

ECMA

EUROPEAN COMPUTER MANUFACTURERS ASSOCIATION

Final Draft

STANDARD ECMA-

DATA INTERCHANGE ON 130 mm
FLEXIBLE DISK CARTRIDGES
USING MFM RECORDING AT 7958 ftprad
ON BOTH SIDES

3,8 TRACKS PER mm

February 1982

TABLE OF CONTENTS

	<u>Page</u>
SECTION I - GENERAL DESCRIPTION AND DEFINITIONS	
SCOPE AND CONFORMANCE	1
SCOPE	1
CONFORMANCE	1
1. GENERAL DESCRIPTION	1
1.1 General Figures	1
1.2 Main Elements	1
1.3 Description	1
1.4 Optional Features	1
1.5 Definitions	2
1.5.1 Flexible Disk	2
1.5.2 Reference Flexible Disk Cartridge	2
1.5.3 Secondary Reference Flexible Disk Cartridge	2
1.5.4 Reference Flexible Disk Cartridge for Recording Field and Signal Amplitude	2
1.5.5 Typical Field	2
1.5.6 Reference Field	2
1.5.7 Test Recording Current	2
1.5.8 Standard Reference Amplitude	3
1.5.9 Average Signal Amplitude	3
1.5.10 In Contact	3
1.5.11 Direction of Rotation	3
1.5.12 Formatting	3
1.5.13 Initialization	3
SECTION II - MECHANICAL AND PHYSICAL CHARACTERISTICS	
2. GENERAL REQUIREMENTS	5
2.1 Environment and Transportation	5
2.1.1 Testing environment	5
2.1.2 Operating environment	5
2.1.3 Storage environment	5
2.1.4 Transportation	6
2.1.5 Handling	6
2.2 Materials	6
2.2.1 Jacket	6
2.2.2 Liner	6
2.2.3 Disk	6
2.2.4 Envelope	6
3. DIMENSIONAL CHARACTERISTICS	6
3.1 Jacket	7
3.1.1 Form	7
3.1.2 Thickness	7
3.1.3 Central windows	7
3.1.4 Index windows	7

TABLE OF CONTENTS (cont'd)

	<u>Page</u>
3.1.5 Head windows	8
3.1.6 Reference Edge profile	8
3.1.7 Construction of the jacket	8
3.1.8 Notches	8
3.1.9 Write-enable notch	8
3.2 Liner	9
3.3 Disk	9
3.3.1 Diameter	9
3.3.2 Thickness	9
3.3.3 Index hole	9
3.3.4 Recording area	9
3.3.5 Sides	9
4. PYHSICAL CHARACTERISTICS	9
4.1 Flammability	9
4.2 Coefficient of Linear Thermal Expansion of the Disk	10
4.3 Coefficient of Linear Hygroscopic Expansion of the Disk	10
4.4 Opacity	10
4.4.1 Opacity of the jacket	10
4.4.2 Opacity of the disk	10
4.5 Torque	10
4.5.1 Starting torque	10
4.5.2 Running torque	10
SECTION III - MAGNETIC CHARACTERISTICS OF THE UNRECORDED FLEXIBLE DISK CARTRIDGE	
5. MAGNETIC CHARACTERISTICS	12
5.1 Track Geometry	12
5.1.1 Number of tracks	12
5.1.2 Width of tracks	12
5.1.3 Track location	12
5.1.4 Track number	12
5.1.5 Index	12
5.2 Functional Testing	12
5.2.1 Surface tests	12
5.2.2 Track quality tests	14
5.2.3 Rejection criteria	14
SECTION IV - TRACK FORMAT	
6. TRACK FORMAT	16
6.1 General Requirements	16
6.1.1 Mode of recording	16
6.1.2 Track location tolerance of the recorded flexible disk cartridge	16

TABLE OF CONTENTS (cont'd)

	<u>Page</u>
6.1.3 Recording offset angle	16
6.1.4 Density of recording	16
6.1.5 Flux transition spacing	16
6.1.6 Average Signal Amplitude	17
6.1.7 Byte	17
6.1.8 Sector	18
6.1.9 Cylinder	18
6.1.10 Cylinder number	18
6.1.11 Data capacity of a track	18
6.1.12 Hexadecimal notation	18
6.1.13 Error Detection Characters (EDC)	18
6.2 Detailed Description of Track Layout after First Formatting for Track 00, Side 0	19
6.2.1 Index Gap	19
6.2.2 Sector Identifier	19
6.2.3 Identifier Gap	20
6.2.4 Data Block	20
6.2.5 Data Block Gap	21
6.2.6 Track Gap	21
6.3 Detailed Description of Track Layout after the First Formatting for all Tracks other than Track 00, Side 0	21
6.3.1 Index Gap	21
6.3.2 Sector Identifier	21
6.3.3 Identifier Gap	22
6.3.4 Data Block	22
6.3.5 Data Block Gap	23
6.3.6 Track Gap	23
6.4 Detailed Description of Track Layout of a Recorded Flexible Disk for Data Interchange	23
6.4.1 Representation of characters	23
6.4.2 Good and bad cylinders	24
6.4.3 Requirements for cylinders	24
6.4.4 Layout of the tracks of a good cylinder	24
6.4.5 Layout of the tracks of a bad cylinder	26
APPENDIX A - MEASUREMENT OF THE CARTRIDGE THICKNESS	32
APPENDIX B - MEASUREMENT OF LIGHT TRANSMITTANCE	34
APPENDIX C - METHOD FOR MEASURING THE EFFECTIVE TRACK WIDTH	38
APPENDIX D - EDC IMPLEMENTATION	39

SECTION I

GENERAL DESCRIPTION AND DEFINITIONS

SCOPE AND CONFORMANCE

SCOPE -

This Standard ECMA- specifies the mechanical, physical and magnetic characteristics of a 130 mm magnetic flexible disk cartridge to provide physical interchangeability between data processing systems. It also specifies the quality of the recorded signals, the track layout and the track format. Together with the labelling system specified in Standard ECMA-67, the track format in this Standard affords for full data interchange between data processing systems.

CONFORMANCE

A 130 mm flexible disk cartridge recorded on both sides is in conformance with this Standard if it meets all mandatory requirements of this Standard.

1. GENERAL DESCRIPTION

1.1 General Figures

A typical flexible disk cartridge is represented in Figs. 1 to 3.

Fig. 1, Flexible Disk Cartridge, shows the cartridge seen from above, Side 0 up.

Fig. 2, Section II-II, is a cross-section along line II-II in Fig. 1.

Fig. 3, Protective Envelope with Cartridge, shows a protective envelope with cartridge, Side 1 up.

1.2 Main Elements

The main elements of this flexible disk cartridge are:

- the recording disk
- the liner
- the jacket

The cartridge is stored in an envelope.

1.3 Description

The jacket shall have a square form. It includes a central window, an index window and a head window in both sides.

The liner is fixed to the inside of the jacket. It comprises two layers of material between which the disk is held. The liner has the same openings as the jacket.

The disk has only a central hole and an index hole.

1.4 Optional Features

The interchange characteristics of the jacket allow for variations of its construction. It may include flaps (e.g. three flaps as shown in the drawings, or none) and notches along the Reference Edge.

1.5 Definitions

For the purpose of this Standard the following definitions apply:

1.5.1 Flexible Disk

A flexible disk which accepts and retains on the specified side or sides magnetic signals intended for input/output and storage purposes of information data processing and associated systems.

1.5.2 Reference Flexible Disk Cartridge

A flexible disk cartridge arbitrarily selected for a given property for calibrating purposes.

1.5.3 Secondary Reference Flexible Disk Cartridge

A flexible disk cartridge intended for routine calibrating purposes, the performance of which is known and stated in relation to that of the Reference Flexible Disk Cartridge.

1.5.4 Reference Flexible Disk Cartridge for Recording Field and Signal Amplitude

A Reference Flexible Disk Cartridge selected as a standard for Recording Field and Signal Amplitude.

On side 0 of this cartridge track 00, having a radius of 57,150 mm and track 79, having a radius of 35,983 mm are declared as reference tracks. To provide a standard for side 1 the same surface is used by turning the disk over in the jacket.

NOTE 1:

The Master Standard for Signal Amplitude will be established by the Physikalisch-Technische Bundesanstalt (PTB), Braunschweig, Germany. Secondary Reference Flexible Disk Cartridges can be ordered from PTB under number RM as long as available.

1.5.5 Typical Field

The minimum recording field which, when applied to a flexible disk cartridge, causes a signal output equal to 95% of the maximum Average Signal Amplitude when taken as a function of the recording field at the specified track and flux transition density of that flexible disk cartridge.

1.5.6 Reference Field

The Reference Field is the typical field of the Reference Flexible Disk Cartridge for Recording Field and Signal Amplitude.

1.5.7 Test Recording Current

The Test Recording Current is the current between 145% and 155% of the current which produces the Reference Field at 125 000 fpts on track 00 of both sides.

1.5.8 Standard Reference Amplitude

The Standard Reference Amplitudes (SRA) are the Average Signal Amplitudes derived from the reference tracks of the Signal Amplitude Reference Flexible Disk Cartridge using the Test Recording Current.

SRA_{1f} is the Average Signal Amplitude from a recording written using 125 000 ftps at a radius of 57,150 mm

SRA_{2f} is the Average Signal Amplitude from a recording written using 250 000 ftps at a radius of 35,983 mm.

1.5.9 Average Signal Amplitude

The Average Signal Amplitude for a track is the arithmetically averaged value of the output voltages measured peak-to-peak over the whole track.

1.5.10 In Contact

An operating condition in which the magnetic surface of the disk intended for data storage is in physical contact with the magnetic heads.

1.5.11 Direction of Rotation

The direction of rotation shall be counterclockwise when looking at side 0.

1.5.12 Formatting

Writing the proper control information establishing the 80 physical cylinders and designating addresses of physical records on the surfaces of the flexible disk.

1.5.13 Initialization

Writing of the Volume Label, the ERMAP label, and any other information initially required to be on the flexible disk cartridge, prior to the commencement of general processing or use.

SECTION II

MECHANICAL AND PHYSICAL CHARACTERISTICS

2. GENERAL REQUIREMENTS

2.1 Environment and Transportation

2.1.1 Testing environment

Tests and measurements made on the cartridge to check the requirements of this Standard shall be carried out under following conditions:

Temperature : $(23 \pm 2) ^\circ\text{C}$

RH : 40% to 60%

Conditioning before testing : 24 hours minimum

The temperature and the RH shall be measured in the air immediately surrounding the cartridge.

The stray magnetic field at any point on the disk surface, including that resulting from the concentrating effect of the recording head, shall not exceed 4000 A/m.

2.1.2 Operating environment

Cartridges used for data interchange shall be operated under the following conditions:

Temperature : $10 ^\circ\text{C}$ to $50 ^\circ\text{C}$

RH : 20% to 80%

Wet bulb temperature : less than $29 ^\circ\text{C}$

The temperature and the RH shall be measured in the air immediately surrounding the cartridge. It is recommended that the rate of change of the temperature should not exceed $20 ^\circ\text{C}$ per hour.

There shall be no deposit of moisture on or in the cartridge. The stray magnetic field at any point on the disk surface, including that resulting from the concentrating effect of the recording head, shall not exceed 4000 A/m.

2.1.3 Storage environment

During storage it is recommended that the cartridges are kept within the following conditions:

Temperature : $4 ^\circ\text{C}$ to $50 ^\circ\text{C}$

RH : 8% to 80%

Each cartridge shall be in an envelope and in an upright position.

The ambient stray magnetic field shall not exceed 4000 A/m.

NOTE 2:

Cartridges which have been stored at temperatures and humidities exceeding the operating conditions may exhibit degraded performance characteristics. Such cartridges should be subjected to a conditioning period of not less than 24 hours within the operating environment prior to use.

2.1.4 Transportation

Responsibility for ensuring that adequate precautions are taken during transportation shall be with the sender. During transportation the cartridge shall be in its envelope and in a protective package. The latter shall be free from dust or extraneous matter. It shall have a clear interior and construction preventing ingress of dust and water. It is recommended that a sufficient space exists between cartridge and outer surface of the final container, so that risk of damage due to stray magnetic fields will be negligible.

It is recommended not to exceed the following conditions:

Temperature : -40 °C to 51,5 °C

Maximum rate of temperature change : 20 °C per hour

RH : 8% to 90%

There should be no deposit of moisture on or in the cartridge.

2.1.5 Handling

The cartridge shall stay out of its envelope for the shortest time possible. When handling the cartridge the operator shall not touch the exposed magnetic surfaces of the disk and shall avoid exposing the cartridge to direct sunlight moisture and dust.

2.2 Materials

2.2.1 Jacket

The jacket may be constructed from any suitable material.

2.2.2 Liner

The material of the liner shall be able to retain dust without damage to the disk.

2.2.3 Disk

The disk may be constructed from any suitable material (e.g. bi-axially oriented polyethylene terephthalate) coated on both sides with a strong and flexible layer of magnetic material (e.g. γ -Fe₂O₃).

2.2.4 Envelope

The envelope may be manufactured from any suitable material (e.g. paper).

3. DIMENSIONAL CHARACTERISTICS

The dimensional characteristics listed in the following clauses are indicated in Figs. 4 to 8.

- Fig. 4 Jacket Dimensions, shows the jacket.
 Fig. 5 Cartridge Thickness, shows a partial cross-section of the jacket.
 Fig. 6 Disk Dimensions, shows the disk.
 Fig. 7 Disk Thickness, shows a cross-section of the disk.
 Fig. 8 Pressure Pad, shows the dimensions.

All dimensions are referred to the Reference Edge of the cartridge (see Fig. 4).

3.1 Jacket

3.1.1 Form

The jacket shall have a square form with angles of $90^\circ \pm 30'$ and a side length

$$l_1 = 133,3 \text{ mm} \pm 0,4 \text{ mm}$$

3.1.2 Thickness

In an area defined by

$$r_1 = 35 \text{ mm}$$

$$r_2 = 50 \text{ mm}$$

and with a probe having a diameter of 15 mm applied against the cartridge with a force of 1 N, the thickness of the jacket wall and liner shall be

$$e_1 = 0,45 \text{ mm} \pm 0,15 \text{ mm}$$

The overall thickness of the cartridge shall be (see also 3.1.7): $1,2 \text{ mm} < e_2 < 2,1 \text{ mm}$, when measured according to Appendix A.

The cartridge shall fall freely through a gauge with a 2,6 mm wide opening having flat, vertical walls and a depth of 150 mm.

3.1.3 Central windows

The central windows shall have a diameter

$$d_1 = 39,7 \text{ mm} \pm 0,2 \text{ mm}$$

The position of their centre is defined by

$$l_2 = 66,65 \text{ mm} \pm 0,30 \text{ mm}$$

3.1.4 Index windows

Location

The centre of the index windows shall be defined

$$l_3 = 42,10 \text{ mm} \pm 0,25 \text{ mm}$$

$$l_4 = 60,00 \text{ mm} \pm 0,25 \text{ mm}$$

Diameter

The diameter of the index windows shall be defined by

$$d_2 = 6,35 \text{ mm} \pm 0,20 \text{ mm}$$

3.1.5 Head windows

Location

The location of the lowest point of the head windows shall be defined by

$$l_5 = 3,30 \text{ mm} \pm 0,25 \text{ mm}$$

Dimensions

The width of the head windows shall be

$$l_6 = 12,7 \text{ mm} \pm 0,2 \text{ mm}$$

The nominal radius of their ends shall

$$r_3 = 6,35 \text{ mm}$$

Their length shall be

$$l_7 = 35,00 \text{ mm} \pm 0,25 \text{ mm}$$

3.1.6 Reference Edge profile

Within an area defined by

$$l_8 = 25 \text{ mm}$$

The Reference Edge shall have a convex profile, e.g. be rounded off with one or more radii of 0,3 mm minimum.

3.1.7 Construction of the jacket

If the jacket utilizes flaps, their width shall not exceed

$$l_9 = 12 \text{ mm}$$

The total thickness e_2 of the cartridge with flaps shall satisfy the conditions of 3.1.2.

3.1.8 Notches

Two notches may be provided along the Reference Edge. If provided, they have to be entirely contained within areas defined by:

$$l_{10} = 48 \text{ mm min.}$$

$$l_{11} = 58 \text{ mm max.}$$

$$l_{12} = 75 \text{ mm min.}$$

$$l_{13} = 85,5 \text{ mm max.}$$

$$l_{14} = 2,0 \text{ mm max.}$$

3.1.9 Write-enable notch

The position and size of the write-enable notch shall be defined by:

$$l_{19} = 96,7 \text{ mm} \pm 0,2 \text{ mm}$$

$$l_{20} = 6,35 \text{ mm} \pm 0,13 \text{ mm}$$

$$l_{21} = 3,8 \text{ mm} \pm 0,2 \text{ mm}$$

If the notch is covered by any means, writing of new information shall be inhibited.

3.2 Liner

The liner shall always cover the recording area (3.3.4). However, no part of the liner shall protrude by more than 0,5 mm into the openings of the jacket.

3.3 Disk

3.3.1 Diameter

The external diameter of the disk shall be:

$$d_3 = 130,2 \text{ mm} \pm 0,2 \text{ mm}$$

The inner diameter of the disk shall be:

$$d_4 = 28,57 \text{ mm} \pm 0,025 \text{ mm}$$

3.3.2 Thickness

The thickness of the disk shall be:

$$e_3 = 0,080 \text{ mm} \pm 0,010 \text{ mm}$$

3.3.3 Index hole

Location

The location of the index hole shall be defined by:

$$r_4 = 25,4 \text{ mm} \pm 0,1 \text{ mm}$$

Diameter

The diameter of the index hole shall be:

$$d_5 = 2,54 \text{ mm} \pm 0,10 \text{ mm}$$

3.3.4 Recording area

The recording area shall be defined on both sides by:

$$r_5 = 34,0 \text{ mm max.}$$

$$r_6 = 57,4 \text{ mm min.}$$

3.3.5 Sides

For convenience of description the two sides are defined as Side 0 and Side 1; they are shown in Figs. 1-4 and Fig. 8.

4. PHYSICAL CHARACTERISTICS

4.1 Flammability

Disk, jacket and/or liner components which ignite from a match flame and when so ignited continue to burn in a still carbon dioxide atmosphere shall not be used.

4.2 Coefficient of Linear Thermal Expansion of the Disk

The coefficient of thermal expansion of the disk shall be:

$$(17 \pm 8) \cdot 10^{-6} \text{ per } ^\circ\text{C}$$

4.3 Coefficient of Linear Hygroscopic Expansion of the Disk

The coefficient of hygroscopic expansion of the disk shall be:

$$(0 \text{ to } 15) \cdot 10^{-6} \text{ per } \% \text{ RH}$$

4.4 Opacity

4.4.1 Opacity of the jacket

The jacket shall have a light transmittance of less than 1% using an LED with a nominal wavelength of 900 nm as the radiation source when measured according to Appendix B.

4.4.2 Opacity of the disk

The disk shall have a light transmittance of less than 1% using an LED with a nominal wavelength of 900 nm as the radiation source when measured according to Appendix B.

4.5 Torque

4.5.1 Starting torque

The starting torque, without heads and pads loaded to the cartridge, shall not exceed 0,01 N.m.

4.5.2 Running torque

When the disk cartridge is tested at a rotation speed of 300 rpm \pm 7 rpm, with a pressure pad of 280 mm² \pm 10 mm² surface applied with a force of 0,70 N \pm 0,05 N and located parallel to the head windows as defined in Fig. 8 by:

$$l_{15} = 45 \text{ mm}$$

$$l_{16} = 55 \text{ mm}$$

$$l_{17} = 7 \text{ mm}$$

$$l_{18} = 35 \text{ mm}$$

the torque necessary to rotate the disk shall be between 0,01 N.m and 0,03 N.m.

SECTION III

MAGNETIC CHARACTERISTICS
OF THE UNRECORDED FLEXIBLE DISK CARTRIDGE

5. MAGNETIC CHARACTERISTICS

5.1 Track Geometry

5.1.1 Number of tracks

There shall be 80 discrete concentric tracks on each side of the disk in the recording area (3.3.4) for data interchange.

5.1.2 Width of tracks

The recorded track width on the disk surface shall be:

$$0,1590 \text{ mm} \pm 0,0063 \text{ mm}$$

The area between the tracks shall be erased. The method of measuring effective track width is given in Appendix C.

5.1.3 Track location

5.1.3.1 Nominal locations

The nominal radius of the centrelines of all tracks shall be calculated by using the formula:

$$R_n = x - \frac{n}{96} \cdot 25,4 \text{ mm}$$

where: n is the track number: n = 00 to 79

x = 57,150 mm for side 0

x = 55,033 mm for side 1.

Therefore, each track on side 1 is offset inwards by eight track positions from the track on side 0 having the same track number.

5.1.3.2 Track location tolerance

The centrelines of the recorded tracks shall be within $\pm 0,025$ mm of the nominal positions, when measured in the testing environment (2.1.1).

5.1.4 Track number

The track number shall be a two-digit decimal number (00 to 79) for each side which identifies the tracks consecutively, starting at the outermost track (00).

5.1.5 Index

The index signal is used only for timing purposes during formatting.

5.2 Functional Testing

For the purpose of the following tests the same drive unit shall be used for writing and reading operations both for the disk under test and for the Signal Amplitude Reference Flexible Disk Cartridge.

5.2.1 Surface tests

The magnetic properties of both data surfaces are defined by the testing requirements given below.

5.2.1.1 Test conditions

The disk shall be tested at 300 rpm \pm 6 rpm. The test frequencies used shall be:

1f = 125 000 ftps \pm 125 ftps

2f = 250 000 ftps \pm 250 ftps

The frequency(ies) to be used is specified for each test.

5.2.1.2 Typical Field

The Typical Field of the disk under test shall be within \pm 20% of the Reference Field. It shall be measured using 1f on tracks 00 and 79 on both sides.

5.2.1.3 Average Signal Amplitude

When the disk under test has been recorded with the Test Recording Current, then read back and compared with the Signal Amplitude Reference Flexible Disk Cartridge recorded under the same conditions, and on the same system, the Average Signal Amplitude shall be:

Side 0, track 00, using 1f : less than 130% of SRA_{1f},

Side 0, track 79, using 2f : more than 80% of SRA_{2f},

Side 1, track 00, using 1f : less than 130% of the Average Signal Amplitude for the track with the same radius (1.5.4),

Side 1, track 71, using 2f : more than 80% of SRA_{2f}.

5.2.1.4 Resolution

After recording, using the Test Recording Current, on track 79 of side 0 and on track 71 of side 1 the ratios:

$$\frac{\text{Average Signal Amplitude Using 2f}}{\text{Average Signal Amplitude Using 1f}}$$

shall be greater than 90% of the same ratios for the Signal Amplitude Reference Flexible Disk Cartridge.

5.2.1.5 Overwrite

On track 00 after recording with the Test Recording Current, first using 1f and then overwriting with 2f for one revolution, the ratio:

$$\frac{\text{Residual Average Signal Amplitude at 1f after overwrite using 2f}}{\text{Average Signal Amplitude after first recording using 1f}}$$

shall be less than 100% of the value of the same ratio for the Standard Amplitude Reference Flexible Disk Cartridge. This test shall be performed on both sides, and a frequency-selective voltmeter shall be used.

5.2.1.6 Modulation

The modulation shall be:

$$\frac{\text{Maximum mean} - \text{Minimum mean}}{\text{Maximum mean} + \text{Minimum mean}} \cdot 100\%$$

The maximum mean shall be the average value of the amplitude modulated output voltage in that part of the track with the maximum amplitudes, and the minimum mean shall be that in the respective part with the minimum amplitudes. Output voltage shall be measured peak-to-peak, averaging shall be done over about 2000 consecutive flux transitions.

On both sides on track 00 using 1f and on track 79 using 2f, modulation shall be less than 10%.

5.2.2 Track quality tests

These tests shall be carried out over all 80 usable tracks at the defined positions on each side. The test Recording Current shall be used.

5.2.2.1 Missing pulse

Write a track at 2f with the Test Recording Current. Any playback signal, when measured base-to-peak, which is less than 40% of half the arithmetically averaged value of the output voltages measured peak-to-peak over the preceding 2000 consecutive flux transitions, shall be a missing pulse.

5.2.2.2 Extra pulse

Write a track at 2f with the Test Recording Current, erase for five revolutions with a constant direct current equivalent to the quiescent value of the Test Recording Current. Any playback signal which, when measured base-to-peak, including the statistical noise and the residual signal of the disk, exceeds 20% of half the Average Signal Amplitude at 2f of the track under test shall be an extra pulse.

5.2.3 Rejection criteria

5.2.3.1 Defective track

A track on which one or more missing and/or extra pulses are detected in the same position(s) on consecutive passes shall be a defective track. The applicable number of consecutive passes shall be a matter for agreement between purchaser and supplier.

5.2.3.2 Requirements for tracks

As initially received from the medium supplier, the cartridge shall have no defective track.

5.2.3.3 Rejected cartridge

A cartridge which does not meet the requirements of 5.2.3.2 shall be rejected.

SECTION IV

TRACK FORMAT

6. TRACK FORMAT

6.1 General Requirements

6.1.1 Mode of recording

6.1.1.1 Track 00, side 0

The mode of recording shall be Two-Frequency ^{WO} where the start of every bit cell is a clock flux transition. A ONE is represented by a data flux transition between two clock flux transitions. ^{Taken by the data}

6.1.1.2 All tracks other than track 00, side 0

The mode of recording ^{SOll} shall be Modified Frequency Modulation (MFM) for which the conditions are:

- i) a flux transition shall be written at the centre of each bit cell containing a ONE, ^{SOll}
- ii) a flux transition shall be written at each cell boundary between consecutive bit cells containing ZEROs. ^{SOll}

6.1.2 Track location tolerance of the recorded flexible disk cartridge

The centrelines of the recorded tracks ^{SOll} shall be within $\pm 0,0425$ mm of the nominal positions. This tolerance corresponds to twice the standard deviation.

6.1.3 Recording offset angle

At the instant of writing or reading a magnetic transition, the transition shall have an angle $\alpha = 31' \pm 18'$ with the radius. This tolerance corresponds to twice the standard deviation (Fig. 9).

6.1.4 Density of recording

6.1.4.1 The nominal density of recording shall be 7958 flux transitions per radian. The nominal bit cell length for track 00, side 0 is 251 microradians, and for all the other tracks it is 125,5 microradians. ^{SOll}

6.1.4.2 The long-term average bit cell length shall be the average bit cell length measured over a sector. It shall be within $\pm 3,5\%$ of the nominal bit cell length. ^{SOll}

6.1.4.3 The short-term average bit cell length, referred to a particular bit cell, shall be the average of the lengths of the preceding eight bit cells. It shall be within $\pm 8\%$ of the long-term average bit cell length. ^{SOll}

6.1.5 Flux transition spacing


6.1.5.1 Flux transition spacing for track 00, side 0

6.1.5.1.1 The spacing between two clock flux transitions surrounding a data flux transition or between two data ^{um -}

flux transitions surrounding a clock flux transition shall be between 90% and 140% of the nominal bit cell length.

6.1.5.1.2 The spacing between two clock flux transitions not surrounding a data flux transition or between two data flux transitions surrounding a missing clock flux transition shall be between 60% and 110% of the nominal bit cell length.

6.1.5.1.3 The spacing between a data flux transition and the preceding clock flux transition (when not missing) or between a clock flux transition and the preceding data flux transition (when not missing) shall be between 45% and 70% of the nominal bit cell length.



6.1.5.2 Flux transition spacing for all tracks other than track 00 side 0

To obtain optimum results in data detection a phase-locked oscillator (PLO) with a nominal averaging time of 64 μ s is required in the Read Chain.

The timing pulses from the PLO will be directly related to the short term average bit cell length and will define the short term average bit cell period at that instant.

The displacement of any flux transition from its nominal position as predicted by the PLO shall not exceed $\pm 20\%$ of the bit cell length as predicted by the PLO.

6.1.6 Average Signal Amplitude

The Average Signal Amplitude on any non-defective track (5.2.3.1) of the interchanged flexible disk cartridge shall be less than 160% of SRA_{1f} and more than 40% of SRA_{2f} .

6.1.7 Byte

A byte is a group of eight bit-positions, identified B_1 to B_8 , with B_8 most significant and recorded first.

The bit in each position is a ZERO or a ONE.

6.1.8 Sector

All tracks are divided into 16 sectors.

6.1.9 Cylinder

A pair of tracks, one on each side, having the same track number.

6.1.10 Cylinder number

The cylinder number shall be a two-digit number ^{coll} identical with the track number of the tracks of the cylinder.

6.1.11 Data capacity of a track

The data capacity of track 00, side 0 shall ^{coll} be 2048 bytes. The data capacity of all tracks other than track 00, side 0 shall be 4096 bytes.

6.1.12 Hexadecimal notation

Hexadecimal notation is used hereafter to denote a number of bytes:

(00) for (B₈ to B₁) = 00000000

(01) for (B₈ to B₁) = 00000001

(FF) for (B₈ to B₁) = 11111111

(FE)* for (B₈ to B₁) = 11111110

where the clock transitions of B₆, B₅ and B₄ are missing.

(FB)* for (B₈ to B₁) = 11111011

where the clock transitions of B₆, B₅ and B₄ are missing.

(FS)* for (B₈ to B₁) = 11111000

where the clock transitions of B₆, B₅ and B₄ are missing.

(4E) for (B₈ to B₁) = 01001110

(FE) for (B₈ to B₁) = 11111110

(FB) for (B₈ to B₁) = 11111011

(F8) for (B₈ to B₁) = 11111000

(A1)* for (B₈ to B₁) = 10100001

where the boundary transition between B₃ and B₄ is missing.

6.1.13 Error Detection Characters (EDC)


The two EDC-bytes are hardware generated by shifting serially the relevant bits, specified later for each part of the track through a 16-bit shift register described by:

$$x^{16} + x^{12} + x^5 + 1$$

(See also Appendix D).

6.2 Detailed ^{Beschreibung} Description of Track Layout after First Formatting for Track 00, Side 0

After first formatting there shall be 16 usable sectors on the track. The layout of the track shall be as follows:



6.2.1 Index Gap

At nominal density this field shall comprise 16 (FF)-bytes. Writing the Index Gap is started when the Index hole is detected. Any of the first 8 bytes may be corrupted due to subsequent overwriting.

6.2.2 Sector Identifier

This field shall be as follows:

SECTOR IDENTIFIER						
IDENTIFIER MARK		ADDRESS IDENTIFIER				
6 Bytes	1 Byte	TRACK ADDRESS		S	1 Byte	EDC
		C	Side	1 Byte		2 Bytes
(00)	(FE)*	1 Byte (00)	1 Byte (00)		(00)	

6.2.2.1 Identifier Mark

This field shall comprise 7 bytes:

- 6 (00)-bytes
- 1 (FE)*-byte

6.2.2.2 Address Identifier

This field shall comprise 6 bytes.

6.2.2.2.1 Track Address

This field shall comprise 2 bytes:

Cylinder Address (C)

This field shall specify in binary notation the cylinder address. It shall be (00) for all sectors.

Side Number (Side)

This field shall specify the side of the disk.
It shall be (00) for all sectors.

6.2.2.2.2 Sector Number (S)

The 3rd byte shall specify in binary notation the sector number from 01 for the 1st sector to 16 for the last sector. The 16 sectors shall be numbered in the natural order: 1, 2, 3, ..., 15, 16.

6.2.2.2.3 4th byte of the Sector Address

The 4th byte shall be always a (00)-byte.

6.2.2.2.4 EDC

These two bytes shall be generated as defined in 6.1.13 using the bytes of the Sector Identifier starting with the (FE)*-byte (6.2.2.1) of the Identifier Mark and ending with the 4th byte (6.2.2.2.3) of the Sector Address.

6.2.3 Identifier Gap

This field shall comprise 11 initially recorded (FF)-bytes.

6.2.4 Data Block

This field shall be as follows:

DATA BLOCK			
DATA MARK		DATA FIELD	EDC
6 Bytes (00)	1 Byte (FB)*	128 Bytes	2 Bytes

6.2.4.1 Data Mark

This field shall comprise:

- 6 (00)-bytes
- 1 (FB)*-byte.

6.2.4.2 Data Field

This field shall comprise 128 bytes. No requirements are implied beyond the correct EDC for the content of this field (see also 6.4.4.2.4.2).

6.2.4.3 EDC

These two bytes shall be generated as defined in 6.1.13 using the bytes of the Data Block starting with the 7th byte of the Data Mark (6.2.4.1) and ending with the last byte of the Data Field (6.2.4.2).

6.2.5 Data Block Gap


- This field shall comprise 24 initially recorded (FF)-bytes it is recorded after each Data Block and it precedes the following Sector Identifier. After the last Data Block it precedes the Track Gap.

6.2.6 Track Gap

This field shall follow the Data Block Gap of the 16th sector. At nominal density it should comprise 149 (FF)-bytes. Writing of the Track Gap takes place until the Index hole is detected, unless it has been detected during writing of the last Data Block Gap, in which case there shall be no Track Gap.

6.3 Detailed Description of Track Layout after the First Formatting for all Tracks other than Track 00, Side 0

After the first formatting there shall be 16 usable sectors on each track. The layout of each track shall be as follows:



6.3.1 Index Gap

At nominal density this field shall comprise 32 (4E)-byte. Writing the Index Gap is started when the Index hole is detected. Any of the first 16 bytes may be corrupted due to subsequent overwriting.

6.3.2 Sector Identifier

This field shall be defined as follows:

SECTOR IDENTIFIER							
IDENTIFIER MARK			ADDRESS IDENTIFIER				
12 Bytes	3 Bytes	1 Byte	TRACK ADDRESS		S	1 Byte	EDC
			C 1 Byte	Side 1 Byte (00) or (01)	1 Byte		2 Bytes
(00)	(A4)*	(FE)	1	1	1	(01)	2

6.3.2.1 Identifier Mark

- This field shall comprise 16 bytes:

12 (00)-bytes
3 (A1)*-bytes
1 (FE)-byte

6.3.2.2 Address Identifier

This field shall comprise 6 bytes.

6.3.2.2.1 Track Address

This field shall comprise 2 bytes:

Cylinder Address (C)

This byte shall specify in binary notation the cylinder address from 00 for the outermost cylinder to 79 for the innermost cylinder. *außer 79*

Side Number (Side)

This byte shall specify the side of the disk. On side 0 it shall be (00) on all tracks. On side 1 it shall be (01) on all tracks.

6.3.2.2.2 Sector Number (S)

This byte shall specify in binary notation the sector number from 01 for the 1st sector to 16 for the last sector. The sectors shall be numbered in the natural order: 1, 2, 3, ..., 15, 16.

6.3.2.2.3 4th Byte

This byte shall always be a (01)-byte.

6.3.2.2.4 EDC

These two bytes shall be generated as defined in 6.1.13 using the bytes of the Sector Identifier starting with the first (A1)*-byte (6.3.2.1) of the Identifier Mark and ending with the 4th byte (6.3.2.2.3) of the Sector Address.

6.3.3 Identifier Gap

This field shall comprise 22 initially recorded (4E)-bytes.

6.3.4 Data Block

This field shall be as follows:

DATA BLOCK				
DATA MARK			DATA FIELD	EDC
12 Bytes (00)	3 Bytes (A1)*	1 Byte (FB)	255 Bytes	2 Bytes

6.3.4.1 Data Mark

This field shall comprise:

12 (00)-bytes
3 (A1)*-bytes
1 (FB)-byte

6.3.4.2 Data Field

This field shall comprise 256 bytes.

Enforce
No requirements are implied beyond the correct EDC for the content of this field (see also 6.4.4.2.4.2).

6.3.4.3 EDC

These two bytes shall be generated as defined in 6.1.13 using the bytes of the Data Block starting with the first (A1)*-byte of the Data Mark (6.3.4.1) and ending with the last byte of the Data Field (6.3.4.2).

6.3.5 Data Block Gap

This field shall comprise *50 decimal* initially recorded (4E)-bytes. It is recorded after each data block and it precedes the following Sector Identifier. After the last Data Block it precedes the Track Gap.

6.3.6 Track Gap

This field shall follow the Data Block Gap of the last sector. At nominal density it should comprise 362 (4E)-bytes.

2 Writing of the Track Gap takes place until the Index hole is detected, unless it has been detected during writing of the last Data Block Gap, in which case there will be no Track Gap.

6.4 Detailed Description of Track Layout of a Recorded Flexible Disk for Data Interchange

6.4.1 Representation of characters

Characters shall be represented by means of the 7-Bit Coded Character Set (Standard ECMA-6) and, where required, by its 7-bit or 8-bit extensions (Standard ECMA-35) or by means

of the 8-bit Coded Character Set (Standard ECMA-43).

Each 7-bit coded character shall be recorded in bit-positions B₇ to B₁ of a byte; bit-position B₈ shall be recorded with bit ZERO.

The relationship shall be as follows:

Bits of the 7-bit combination	0	b ₇	b ₆	b ₅	b ₄	b ₃	b ₂	b ₁
Bit-positions in the byte	B ₈	B ₇	B ₆	B ₅	B ₄	B ₃	B ₂	B ₁

Each 8-bit coded character shall be recorded in bit-position B₈ to B₁ of a byte.

The relationship shall be as follows:

Bits of the 8-bit combination	b ₈	b ₇	b ₆	b ₅	b ₄	b ₃	b ₂	b ₁
Bit-positions in the byte	B ₈	B ₇	B ₆	B ₅	B ₄	B ₃	B ₂	B ₁

6.4.2 Good and bad cylinders

A good cylinder is a cylinder which has both tracks formatted according to 6.4.4.

A bad cylinder is a cylinder which has both tracks formatted according to 6.4.5.

6.4.3 Requirements for cylinders

Cylinder 00 shall be a good cylinder and shall have no defective sectors on side 0. There shall be at least 77 good cylinders between cylinder 01 and cylinder 79.

6.4.4 Layout of the tracks of a good cylinder

References to sub-clauses of 6.2 are for track 00, side 0. References to sub-clauses of 6.3 are for all other tracks.

6.4.4.1 Index Gap

Description: see 6.2.1 and 6.3.1.

6.4.4.2 Sector Identifier

6.4.4.2.1 Identifier Mark

Description: see 6.2.2.1 and 6.3.2.1.

6.4.4.2.2 Address Identifier

This field shall comprise 6 bytes.

6.4.4.2.2.1 Track Address

This field shall comprise 2 bytes:

Cylinder Address (C)

This field shall specify in binary notation the cylinder address from 00 for the outermost cylinder to 79 for the innermost cylinder.

- If there is no bad cylinder, the cylinder address is identical to the cylinder number.
- If there are one or two bad cylinders, they are skipped and the cylinder address numbering continues sequentially with the next good cylinder. In this case the cylinder address differs by 1 (or 2) from the cylinder number.

Side Number (Side)

Description: see 6.2.2.2.1 and 6.3.2.2.1.

6.4.4.2.2.2 Sector Number (S)

Description: see 6.2.2.2.2 and 6.3.2.2.2.

6.4.4.2.2.3 4th byte

Description: see 6.2.2.2.3 and 6.3.2.2.3.

6.4.4.2.2.4 EDC

Description: see 6.2.2.2.4 and 6.3.2.2.4.

6.4.4.2.3 Identifier Gap

Description: see 6.2.3 and 6.3.3. These bytes may subsequently become corrupted due to overwriting process.

6.4.4.2.4 Data Block

6.4.4.2.4.1 Data Mark

For track 00, side 0, this field shall comprise:

6 (00)-bytes
1 byte

The 7th byte shall be either:

(FB)* indicating that the data is valid and that the whole Data Field can be read, or

(F8)* indicating that the first byte of the Data Field shall be interpreted according to Standard ECMA-67, 130 mm Flexible Disk Cartridge Labelling and File Structure for Information Interchange.

For all other tracks this field shall comprise:

12 (00)-bytes
3 (A1)*-bytes
1 byte

shall then be indicated
The 16th byte shall be either:

(FB) indicating that the data is valid and that the whole Data Field can be read, or

(F8) indicating that the first byte of the Data Field shall be interpreted according to Standard ECMA-67, 130 mm Flexible Disk Cartridge Labelling and File Structure for Information Interchange.

6.4.4.2.4.2 Data Field

This field shall contain a number of bytes as specified in sections 6.2.4.2 or 6.3.4.2.

If it comprises less than the requisite number of data bytes, the remaining positions shall be filled with (00)-bytes.

Data Fields in cylinder 00 are reserved for operating system use, including labelling.

6.4.4.2.4.3 EDC

Description: see 6.2.4.3 and 6.3.4.3.

If the last byte of the Data Mark is (F8)* or (F8) and the 1st character of the Data Field is either CAPITAL LETTER F or FULL STOP, the EDC may or may not be correct, as the sector contains a defective area. If the 1st character is CAPITAL LETTER D, then the EDC shall be correct.

On track 00, side 0, only CAPITAL LETTER D is allowed.

6.4.4.2.5 Data Block Gap

This field is recorded after each Data Block and it precedes the following Sector Identifier. After the last Data Block it precedes the Track Gap.

It comprises initially 24 (FF)-bytes (6.2.5) or 48 (4E)-bytes (6.3.5). These bytes may subsequently become corrupted due to the overwriting process.

6.4.4.2.6 Track Gap

Description: see 6.2.6 and 6.3.6.

6.4.5 Layout of the tracks of a bad cylinder

6.4.5.1 Contents of the fields

The fields of the tracks of a bad cylinder should have the following contents.

6.4.5.1.1 Index Gap

This field should comprise 32 (4E)-bytes.

6.4.5.1.2 Sector Identifier

This field should comprise an Identifier Mark and an Address Identifier.

6.4.5.1.2.1 Identifier Mark

This field should comprise 16 bytes:

12 (00)-bytes
3 (A1)*-bytes
1 (FE)-byte

6.4.5.1.2.2 Address Identifier

This field should comprise 6 bytes:

4 (FF)-bytes
2 EDC-bytes

These two EDC-bytes shall be generated as defined in 6.1.14 using the bytes of the Sector Identifier starting with the first (A1)*-byte (6.4.5.1.2.1) of the Identifier Mark and ending with the above 4 (FF)-bytes.

6.4.5.1.3 Identifier Gap

This field should comprise 22 (4E)-bytes.

6.4.5.1.4 Data Block

6.4.5.1.4.1 Data Mark

This field should comprise 16 (4E)-bytes:

6.4.5.1.4.2 Data Field

This field should contain 256 (4E)-bytes.

6.4.5.1.4.3 EDC

This field should comprise 2 (4E)-bytes.

6.4.5.1.5 Data Block Gap

This field should comprise 48 (4E)-bytes.

6.4.5.1.6 Track Gap

Description: see 6.3.6.

6.4.5.2 Requirements for tracks

Each track of a bad cylinder shall have at least one of its Sector Identifiers with the content specified in 6.4.5.1.2. If this condition is not satisfied the cartridge shall be rejected. All other fields of these tracks can be corrupted.